

BS EN3 Powder Type Fire Extinguisher



ISO 9001:2000



- * British Standards Institution - BSI approval store powder and cartridge type.
- * Suitable for Class A, B, C & electrical hazards.
- * Ideal for industrial, commercial and domestic environment.
- * High quality and good value.
- * Colour coded for instant recognition.
- * All units tested by electronic leak detection.
- * Operated effectively at both high and low temperature.
- * ISO 9001:2000 Certified Quality System by QAS Australia.

<p>CLASS A CARBONACEOUS MATERIALS</p>	<p>CLASS B FLAMMABLE LIQUID</p>	<p>CLASS C FLAMMABLE GAS</p>	<p>SAFE USE ON ELECTRICAL HAZARDS</p>
---	-------------------------------------	----------------------------------	---------------------------------------

TECHNICAL SPECIFICATION

EXTINGUISHER TYPE	1kg	2kg	4kg	6kg	9kg	6kg	9kg	12kg
	STORE PRESSURE TYPE (NITROGEN PROPELLANT)					CO2 CARTRIDGE		
MODEL NO.	FEX108	FEX104	FEX105	FEX106	FEX107	FEX109	FEX110	FEX115
FIRE RATING	5A, 21B	8A, 34B	13A, 70B	21A, 113B	27A, 144B	34A, 233B	43A, 233B	55A, 233B
OPERATING TEMPERATURE	-20°C to 60°C							
OPERATING PRESSURE	12 Bar	14 Bar						
HEIGHT	335mm	400mm	490mm	490mm	555mm	490mm	570mm	605mm
FULL WEIGHT	2.0kg	3.3kg	7.1kg	9.1kg	12.8kg	10.5kg	14.2kg	19.0kg
TEST PRESSURE	25 Bar							
DISCHARGE TIME (S)	6-10 secs	8-12 secs	11-15 secs	17-21 secs	20-24 secs	20-24 secs	23-27 secs	25-32 secs
RANGE OF THROW (approx)	4 - 5 M	4 - 5 M	5 - 6 M	5 - 6 M	5 - 6 M	5 - 6 M	5 - 6 M	5 - 6 M
CARTON SIZE mm	105 x 120 x 345	125 x 160 x 430	180 x 210 x 495	180 x 200 x 485	200 x 200 x 565	180 x 210 x 495	205 x 205 x 590	215 x 215 x 630